

T10 bulb Series



Remark:

- ⦿ Adopts high end silica gels and ceramic
- ⦿ Imported COB/SMD LEDs
- ⦿ Customized Constant Current driver solution
 - Dimmable
 - 9-15VAC/DC
 - Compatible for different specialized transformers to landscape light
- ⦿ Suitable for damp location

RD-T10-COB-2W-BT

Real Power	1.5W
Light Source	1505 COB LEDs
Lumen	210Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	9-15V AC/DC

Icons: Ra >80, Dimmable, 9-15V AC/DC, Damp Location

RD-T10-COB-2W-AF

Real Power	1.5W
Light Source	1505 COB LEDs
Lumen	200Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	9-15V AC/DC

Icons: Ra >80, Dimmable, 9-15V AC/DC, Damp Location

RD-T10-COB-3W

Real Power	2.8W
Light Source	1508 COB LEDs
Lumen	350Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	9-15V AC/DC

Icons: Ra >80, Dimmable, 9-15V AC/DC, Damp Location

RD-T10-2W-SG

Real Power	2W
Light Source	24pcs 2835 SMD
Lumen	180Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	9-15V AC/DC

Icons: Ra >80, Dimmable, 9-15V AC/DC, Damp Location

RD-T10-3W-SG

Real Power	2.5W
Light Source	36pcs 2835 SMD
Lumen	220Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	9-15V AC/DC

Icons: Ra >80, Dimmable, 9-15V AC/DC, Damp Location

RD-T10-CP-5W(01)

Real Power	3W
Light Source	48pcs 2835 SMD
Lumen	320Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	9-15V AC/DC

Icons: Ra >80, Dimmable, 9-15V AC/DC, Damp Location

Attention:

- ⦿ Lifespan of the bulbs will be effected while working ambient temperature that higher 45°C/113°F.
- ⦿ The inner space of enclosed fixtures should be 5 times bigger than the size of the bulbs.
- ⦿ The dimming level for dimmable products would be under a certain dimmer, it is better to take samples for testing the dimming function.